

Mathematical Modelling of Palm Nut

Cracking based on Hertz's Theory

Author(s): OA Koya, MO Faborode

Abstract

A mathematical model based on [Hertz's theory](#) of [contact stress](#) was developed for the prediction of force required to break the palm nut.

Using nuts subjected to a uniaxial compression stress, in their lateral axis between rigid [parallel plates](#), and those propelled to impinge a rigid cylindrical seat along its lateral axis, experimental verification of the model was conducted comparing the theoretical predictions with

estimates from the representations of [conventional methods](#) employed in nut cracking. Properties including size, shape and mass, required in the derived model were determined for two varieties of the palm

nut. [Material stiffness](#) was obtained from the force–deformation curve.

Regression analysis showed an exponential variation of the cracking force with nut [deformation](#). Material stiffness obtained was 654 N/mm and 303 N/mm for the ‘Dura’ and ‘Tenera’ nuts, respectively. The respective ranges of geometric mean diameters were 17.07–27.68 mm and 22.32–

26.51 mm. There was no significant variation of nut [sphericity](#) with size or variety.

Force prediction from the Hertzian model proposed gave good prediction of cracking force that was not significantly different from that obtained from a centrifugal nutcracker driven at 1500 min⁻¹, with a 40 cm diameter cracking chamber

Keywords: Modelling of Palm Nut, Cracking, Palm Nut, Hertz's Theory Journal of [Biosystems Engineering](#)

DOI: <https://doi.org/10.1016/j.biosystemseng.2005.05.011>

Published by: Academic Press in 8/1993